

Serial No. 10/606,441
DeClerck et al
Case No. CE10654R

Amendments to the Claims:

1. (Currently Amended) A method in a wireless communication system for mitigating power-control errors during a soft handoff of a mobile unit, the method comprising:

programming a plurality of base stations with a uniform power-control bit pattern to be sent to the mobile unit during a plurality of power-control bit times, before the mobile unit is acquired on a reverse link; and

timing transmissions of the uniform power-control bit pattern such that the plurality of base stations, when transmitting for use during the soft handoff of the mobile unit, send identical power-control bits during each of the plurality of power-control bit times.

2. (Original) The method of claim 1,

wherein programming the plurality of base stations with the uniform power-control bit pattern comprises programming a pattern that requires more than a single transmission frame of a forward link from a base station to the mobile unit before the pattern repeats, and

wherein timing the transmissions comprises synchronizing the transmissions from each of the plurality of base stations such that the transmissions start at substantially identical times.

BEST AVAILABLE COPY

Serial No. 10/606,441
DeClerck et al
Case No. CE10654R

3. (Original) The method of claim 1,

wherein programming the plurality of base stations with the uniform power-control bit pattern comprises programming a pattern that repeats after a single one of a plurality of transmission frames of a forward link from the base station to the mobile unit, and

wherein timing the transmissions comprises starting the transmissions at substantially identical points within different ones of the plurality of transmission frames.

4. (Original) The method of claim 1,

wherein programming the plurality of base stations with the uniform power-control bit pattern comprises programming a pattern that repeats after a single one of a plurality of transmission frames of a forward link from the base station to the mobile unit, and

wherein timing the transmissions comprises starting the transmissions at substantially identical points within a specific one of the plurality of transmission frames.

5. (Original) The method of claim 1,

wherein timing the transmissions comprises synchronizing the transmissions through a synchronization signal made available to the plurality of base stations.

Serial No. 10/606,441
DeClerck et al
Case No. CE10654R

6. (Currently Amended) An apparatus for use in a wireless communication system for mitigating power-control errors during a soft handoff of a mobile unit, the apparatus for use with a base station of a plurality of base stations attempting to communicate with the mobile unit, the apparatus comprising:

a processor for controlling the base station;

a memory element coupled to the processor for programming the processor, the memory element comprising a uniform power-control bit pattern to be sent by different ones of the plurality of base stations to the mobile unit during a plurality of power-control bit times, before the mobile unit is acquired on a reverse link; and

a synchronizer coupled to the processor for cooperating with the processor to time transmissions of the uniform power-control bit pattern such that the plurality of base stations, when transmitting for use during the soft handoff of the mobile unit, send identical power-control bits during each of the plurality of power-control bit times.

7. (Original) The apparatus of claim 6,

wherein the uniform power-control bit pattern is a pattern that requires more than a single transmission frame of a forward link from the base station to the mobile unit before the pattern repeats, and

wherein the synchronizer is arranged and programmed such that the transmissions of the uniform power-control bit pattern from the plurality of base stations start at substantially identical times.

Serial No. 10/606,441
DeClerck et al
Case No. CE10654R

8. (Original) The apparatus of claim 6,

wherein the uniform power-control bit pattern is a pattern that repeats after a single one of a plurality of transmission frames of a forward link from the base station to the mobile unit, and

wherein the synchronizer is arranged and programmed such that the transmissions of the uniform power-control bit pattern from the plurality of base stations start at substantially identical points within different ones of the plurality of transmission frames.

9. (Original) The apparatus of claim 6,

wherein the uniform power-control bit pattern is a pattern that repeats after a single one of a plurality of transmission frames of a forward link from the base station to the mobile unit, and

wherein the synchronizer is arranged and programmed such that the transmissions of the uniform power-control bit pattern from the plurality of base stations start at a substantially identical point within a specific one of the plurality of transmission frames.

10. (Original) The apparatus of claim 6,

wherein the synchronizer is arranged and programmed to synchronize the transmissions through a synchronization signal made available to the plurality of base stations.

Serial No. 10/606,441
DeClerck et al
Case No. CE10654R

11. (Currently Amended) A base station for use in a wireless communication system for mitigating power-control errors during a soft handoff of a mobile unit, the base station being one of a plurality of base stations attempting to communicate with the mobile unit, the base station comprising:

a processor for controlling the base station;

a wireless transceiver coupled to the processor for providing wireless communications for the base station;

a memory element coupled to the processor for programming the processor, the memory element comprising a uniform power-control bit pattern to be sent by different ones of the plurality of base stations to the mobile unit during a plurality of power-control bit times, before the mobile unit is acquired on a reverse link; and

a synchronizer coupled to the processor for cooperating with the processor to time transmissions of the uniform power-control bit pattern such that the plurality of base stations, when transmitting for use during the soft handoff of the mobile unit, send identical power-control bits during each of the plurality of power-control bit times.

12. (Original) The base station of claim 11,

wherein the uniform power-control bit pattern is a pattern that requires more than a single transmission frame of a forward link from the base station to the mobile unit before the pattern repeats, and

Serial No. 10/606,441
DeClerck et al
Case No. CE10654R

wherein the synchronizer is arranged and programmed such that the transmissions of the uniform power-control bit pattern from the plurality of base stations start at substantially identical times.

13. (Original) The base station of claim 11,

wherein the uniform power-control bit pattern is a pattern that repeats after a single one of a plurality of transmission frames of a forward link from the base station to the mobile unit, and

wherein the synchronizer is arranged and programmed such that the transmissions of the uniform power-control bit pattern from the plurality of base stations start at substantially identical points within different ones of the plurality of transmission frames.

14. (Original) The base station of claim 11,

wherein the uniform power-control bit pattern is a pattern that repeats after a single one of a plurality of transmission frames of a forward link from the base station to the mobile unit, and

wherein the synchronizer is arranged and programmed such that the transmissions of the uniform power-control bit pattern from the plurality of base stations start at a substantially identical point within a specific one of the plurality of transmission frames.

Serial No. 10/606,441
DeClerck et al
Case No. CE10654R

15. (Original) The base station of claim 11,

wherein the synchronizer is arranged and programmed to
synchronize the transmissions through a synchronization signal made available to the
plurality of base stations.

16. (Currently Amended) A wireless communication system infrastructure for
mitigating power-control errors during a soft handoff of a mobile unit, the infrastructure
comprising:

a central controller for controlling the communication system
infrastructure; and

a plurality of base stations coupled to the central controller for
handling communications of the infrastructure, wherein a base station of the plurality of
base stations comprises:

a processor for controlling the base station;

a wireless transceiver coupled to the processor for providing
wireless communications for the base station;

a memory element coupled to the processor for programming the
processor, the memory element comprising a uniform power-control bit pattern to be sent
by different ones of the plurality of base stations to the mobile unit during a plurality of
power-control bit times, before the mobile unit is acquired on a reverse link; and

a synchronizer coupled to the processor for cooperating with the
processor to time transmissions of the uniform power-control bit pattern such that the
plurality of base stations, when transmitting for use during the soft handoff of the mobile

Serial No. 10/606,441
DeClerck et al
Case No. CE10654R

unit, send identical power-control bits during each of the plurality of power-control bit times.

17. (Original) The infrastructure of claim 16,

wherein the uniform power-control bit pattern is a pattern that requires more than a single transmission frame of a forward link from the base station to the mobile unit before the pattern repeats, and

wherein the synchronizer is arranged and programmed such that the transmissions of the uniform power-control bit pattern from the plurality of base stations start at substantially identical times.

18. (Original) The infrastructure of claim 16,

wherein the uniform power-control bit pattern is a pattern that repeats after a single one of a plurality of transmission frames of a forward link from the base station to the mobile unit, and

wherein the synchronizer is arranged and programmed such that the transmissions of the uniform power-control bit pattern from the plurality of base stations start at substantially identical points within different ones of the plurality of transmission frames.

Serial No. 10/606,441
DeClerck et al
Case No. CE10654R

19. (Original) The infrastructure of claim 16,

wherein the uniform power-control bit pattern is a pattern that repeats after a single one of a plurality of transmission frames of a forward link from the base station to the mobile unit, and

wherein the synchronizer is arranged and programmed such that the transmissions of the uniform power-control bit pattern from the plurality of base stations start at a substantially identical point within a specific one of the plurality of transmission frames.

20. (Original) The infrastructure of claim 16,

wherein the synchronizer is arranged and programmed to synchronize the transmissions through a synchronization signal made available to the plurality of base stations.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.